

Nayax M2M Solution for Cashless & Telemetry

- ARM Technology - Cortex , 32Bit, 168Mega Hertz
- Vending Industry Standards: MDB Interface
DEX/DDCMP (EVA DTS)
VCCS
- Quad band GSM/GPRS/CDMA
- Certificates: FCC, CE, PCI, EMV, PTCRB, RoHS
- High Security Encryption System: AES/DES/RSA/SSL
- Multilanguage Support - LCD text & Voice Audio
- External flash up to 16 MB
- Menu navigation and service functionalities
- Peripheral Port: mini USB (Host/Device), Ethernet with external Wi-Fi capability
 - 1 X Reader interface
 - 2 X RS232 interface (RS232 or TTL level manageable through software)
 - 2 X Pulse input/output interfaces + pulse input (Inhibit)
 - 2 X Sensors - door Open, temperature sensor
 - 1 X RS485
- MDB Spy - Capture and analyze messages from all MDB peripherals
- Remote software update
- Physical dimensions: H - 116mm, W - 65mm , D - 30mm, weight – 140 grams
- Power supply: input 10 - 42 Volt DC, 10 – 24 Volt AC, External output 8 Volt DC
- Power consumption 0.3 watt (Idle State) - 1watt (online)
- 2 X Super capacitors - for power down alert (optional)
- Electrostatic discharge: IEC 61000-4-2, level 4 (ESD)
- International Protection Rating: IP50
- Easy installation - Device attached to the machine by 2 built in magnets



Nayax M2M Solution for Cashless & Telemetry



Physical Dimensions

- H - 116mm
- D - 30mm
- W - 65mm

Weight - 140 grams

Operating Temperature:

-30°C ~ 50°C (-22°F - 122°F), Humidity: 5% ~ 95% (non-Condense)

Storage Temperature:

-40°C ~ 60°C (-40°F - 140°F), Humidity: 5% ~ 95% (non-Condense)

